

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Chemetall
expect more⁺

Adrox 8901W,Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

SECTION 1. IDENTIFICATION

Product name : Adrox 8901W,Aerosol NA (12x16oz)
Product code : 000000000050559109

Manufacturer or supplier's details

Company:

Chemetall U.S., Inc.
675 Central Avenue
New Providence, NJ 07974 – USA
+1 800 526-4473
sds.na-chemetall@basf.com

Emergency telephone : CHEMTREC: 800-424-9300, +1-703-527-3887

Recommended use of the chemical and restrictions on use

Restrictions on use : Uses other than recommended

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
STOT SE	3 (May cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
Carc.	2	Carcinogenicity
Repr.	1 (unborn child)	Reproductive toxicity
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Flam. Aerosol	1	Flammable aerosols

Label elements

Pictogram:



Signal Word:
Danger

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Chemetall
expect more⁺

Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

Hazard Statement:

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360	May damage the unborn child.
H402	Harmful to aquatic life.
H373	May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P251	Do not pierce or burn, even after use.
P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P202	Do not handle until all safety precautions have been read and understood.
P211	Do not spray on an open flame or other ignition source.
P240	Ground and bond container and receiving equipment.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P264	Wash contaminated body parts thoroughly after handling.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe mist or vapour or spray.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P337 + P313	If eye irritation persists: Get medical attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P370 + P378	In case of fire: Use water spray for extinction.

Precautionary Statements (Storage):

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Chemetall
expect more⁺

Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

Container is under pressure. Protect from sun and temperatures above 50 °C. Do not open with force or incinerate even after use. Do not spray into flames or onto glowing objects.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Acetone

CAS Number: 67-64-1
Content (W/W): ≥ 25.0 - $< 50.0\%$
Synonym: 2-Propanone Acetone; Dimethyl ketone

propane

CAS Number: 74-98-6
Content (W/W): ≥ 10.0 - $< 15.0\%$
Synonym: Propan

Methylethylketone

CAS Number: 78-93-3
Content (W/W): ≥ 7.0 - $< 10.0\%$
Synonym: Methyl ethyl ketone

Propane, 2-methyl-

CAS Number: 75-28-5
Content (W/W): ≥ 7.0 - $< 10.0\%$
Synonym: 2-Methylpropane; Isobutane

Toluene

CAS Number: 108-88-3
Content (W/W): ≥ 7.0 - $< 10.0\%$
Synonym: Benzene, methyl-

Titanium dioxide

CAS Number: 13463-67-7
Content (W/W): ≥ 7.0 - $< 10.0\%$

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

Synonym: No data available.

talc

CAS Number: 14807-96-6
Content (W/W): ≥ 3.0 - $< 5.0\%$
Synonym: hydrated magnesium silicate

1-methoxy-2-propylacetate

CAS Number: 108-65-6
Content (W/W): ≥ 1.0 - $< 3.0\%$
Synonym: 2-Methoxy-1-methylethyl acetate; 1-Methoxy-2-propyl acetate

2-methoxypropyl acetate

CAS Number: 70657-70-4
Content (W/W): ≥ 0.1 - $< 0.2\%$
Synonym: 2-Methoxypropyl acetate

4. First-Aid Measures

Description of first aid measures

General advice:

Keep warm, calm and covered up. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

If on skin:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

If in eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

If swallowed:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: Acetone

Symptoms: Overexposure may cause:, Eye irritation, irritates the eyes and respiratory tract, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, CNS depression

Information on: propane

Symptoms: Overexposure may cause:, unconsciousness, asphyxia, respiratory disorders, headache, dizziness

Information on: Methyl ethyl ketone

Symptoms: Overexposure may cause:, unconsciousness, vomiting, weakness, peripheral neuropathy, nausea, headache, dizziness

Information on: Toluene

Symptoms: Overexposure may cause:, unconsciousness, death, dilation of pupils, coordination disorder, lethargy, confusion, headache, dizziness, lacrimation

Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote:	No known specific antidote.
Treatment:	Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon oxides
Cool containers exposed to fire with water. Decomposition, pressure build-up and bursting of containers may occur.

Advice for fire-fighters

Protective equipment for fire-fighting:
Appropriate breathing apparatus may be required.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Chemetall
expect more⁺

Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Handle with care - avoid bumps, friction and impact. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

Suitable materials for containers: Paper/Fibreboard, Aluminium, Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage duration: 60 Months

Spraying efficiency of aerosol cans can decrease over time due to e.g. slight propellant loss.

Required time to properly redisperse particles in the can via shaking increases with elapsed shelf life.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Acetone	ACGIH, US:	TWA value 250 ppm ;
	ACGIH, US:	STEL value 500 ppm ;
	OSHA Z1:	PEL 1,000 ppm 2,400 mg/m3 ;
propane	OSHA Z1:	PEL 1,000 ppm 1,800 mg/m3 ;
	ACGIH, US:	; D: Simple asphyxiant, EX: Explosion hazard
Propane, 2-methyl-	ACGIH, US:	STEL value 1,000 ppm ; Explosion hazard.
Methylethylketone	ACGIH, US:	STEL value 300 ppm ;
	ACGIH, US:	TWA value 200 ppm ;
	OSHA Z1:	PEL 200 ppm 590 mg/m3 ;
Toluene	ACGIH, US:	TWA value 20 ppm ;
	OSHA Z2:	max. conc. 500 ppm ;
	OSHA Z2:	CLV 300 ppm ;
	OSHA Z2:	TWA value 200 ppm ;

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

talc	ACGIH, US:	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
	OSHA Z3:	TWA value 20 millions of particles per cubic foot of air ;
	OSHA Z3:	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.
	OSHA Z3:	TWA value 0.1 mg/m3 Respirable ; The exposure limit is calculated from the equation, $10mg/m3/(\%SiO_2+2)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.
Silicon dioxide	ACGIH, US:	TWA value 10 mg/m3 Inhalable particles ;
	ACGIH, US:	TWA value 3 mg/m3 Respirable particles ;
	OSHA Z3:	TWA value 15 mg/m3 Total dust ;
	OSHA Z3:	TWA value 5 mg/m3 Respirable fraction ;
	OSHA Z3:	TWA value 50 millions of particles per cubic foot of air Total dust ;
	OSHA Z3:	TWA value 15 millions of particles per cubic foot of air Respirable fraction ;
	OSHA Z3:	TWA value 0.8 mg/m3 ; The exposure limit is calculated from the equation, $80mg/m3/(\%SiO_2)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.
Titanium dioxide	OSHA Z3:	TWA value 20 millions of particles per cubic foot of air ;
	ACGIH, US:	TWA value 2.5 mg/m3 Respirable finescale particles ;
	ACGIH, US:	TWA value 0.2 mg/m3 Respirable nanoscale particles ;
	OSHA Z1:	PEL 15 mg/m3 Total dust ;

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Chemetall
expect more⁺

Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1), nitrile rubber (NBR) - 0.4 mm coating thickness, butyl rubber (butyl) - 0.7 mm coating thickness, Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1, The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties)., The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures:

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form:	aerosol
Odour:	No data available.
Odour threshold:	No applicable information available.
Colour:	white
pH value:	substance/mixture is a gas
Melting point:	Study technically not feasible.
Freezing point:	not determined
onset of boiling:	57 °C (calculated)
Boiling range:	not determined
Sublimation point:	No applicable information available.
Flash point:	-18 °C (ISO 3679)
	without propellant
Flammability:	Extremely flammable aerosol.
Lower explosion limit:	2.6 %(V)
Upper explosion limit:	12.8 %(V)
Autoignition:	465.00 °C
Vapour pressure:	(20 °C)
	not determined
Density:	0.996 g/cm ³
	(20 °C)
	The values mentioned are those of the active ingredient.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Chemetall
expect more⁺

Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

Relative density:	No applicable information available.
Vapour density:	Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	(23 °C) not applicable
Solubility in water:	insoluble
Miscibility with water:	immiscible
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Risk of bursting. Vapours may form explosive mixture with air.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid direct sunlight.

Incompatible materials

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

Decomposition products:

Possible decomposition products: When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced.,
No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Oral

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

Type of value: ATE

Value: > 20 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation.

Information on: Acetone

Assessment of irritating effects: Irritating to eyes. Not irritating to the skin. Repeated exposure may cause skin dryness or cracking.

Information on: Methyl ethyl ketone

Assessment of irritating effects: Irritating to eyes. Not irritating to the skin. Repeated exposure may cause skin dryness or cracking. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Chemetall
expect more⁺

Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: Acetone

Assessment of repeated dose toxicity: The substance may cause damage to the testes after repeated ingestion of high doses, as shown in animal studies. The substance may cause damage to the hematological system after repeated ingestion of high doses. The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies.

Information on: 1-methoxy-2-propylacetate

Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.

Information on: Toluene

Assessment of repeated dose toxicity: Repeated exposure to large quantities may affect certain organs. Damages the central nerve system. The substance may cause deafness after repeated inhalation.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591	Date of first issue: 02.03.2025
		09	

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Information on: Acetone

Assessment of reproduction toxicity: As shown in animal studies, the product may cause damage to the testes after repeated high exposures that cause other toxic effects.

Teratogenicity

Assessment of teratogenicity: The substance caused malformations/developmental toxicity in laboratory animals.

Information on: Toluene

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

No data available concerning biodegradation and elimination.

Bioaccumulative potential

Bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

No data available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

USDOT

Hazard class:	2.1
ID number:	UN 1950
Hazard label:	2.1
Proper shipping name:	AEROSOLS

Sea transport

IMDG

Hazard class:	2.1
ID number:	UN 1950
Hazard label:	2.1
Marine pollutant:	NO
Proper shipping name:	AEROSOLS

Air transport

IATA/ICAO

Hazard class:	2.1
ID number:	UN 1950
Hazard label:	2.1
Proper shipping name:	AEROSOLS, FLAMMABLE

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number

108-88-3

Chemical name

Toluene

CERCLA RQ

100 LBS

CAS Number

74-98-6; 75-28-5;
64742-47-8;

Chemical name

propane; Propane, 2-methyl-; Distillates, petroleum;
Solvent naphtha (petroleum), medium aliph.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W, Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

1000 LBS	64742-88-7	Toluene
5000 LBS	108-88-3	Acetone
	67-64-1	

State regulations

State RTK

	<u>CAS Number</u>	<u>Chemical name</u>
NJ	67-64-1	Acetone
	74-98-6	propane
	75-28-5	Propane, 2-methyl-
	108-88-3	Toluene
	14807-96-6	talc
PA	13463-67-7	Titanium dioxide
	78-93-3	Methylethylketone
	67-64-1	Acetone
	74-98-6	propane
	75-28-5	Propane, 2-methyl-
	108-88-3	Toluene
	14807-96-6	talc
	7631-86-9	Silicon dioxide
	13463-67-7	Titanium dioxide

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including BENZENE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 2 Fire: 4 Reactivity: 1 Special:

HMIS III rating

Health: 2 α Flammability: 4 Physical hazard: 1

16. Other Information

SDS Prepared by:

Chemetall (now part of BASF Group) NA Product Regulations
SDS Prepared on: 03/02/2025

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Adrox 8901W,Aerosol NA (12x16oz)

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03/02/2025	0000000000505591 09	Date of first issue: 02.03.2025

