



Standard and Advanced - Feature Comparison	Standard (1)	Advanced (3)
		
PosiTector body features	Standard (1)	Advanced (3)
Accepts all PosiTector SPG, DPM and 6000 probes.	●	●
Hi Contrast LCD Display	Monochrome	Color
USB port for fast, simple connection to a PC and to supply continuous power. USB cable included	●	●
USB mass storage ó stored readings and graphs can be accessed using universal PC/Mac web browsers or file explorers. No software required	●	●
Connects to PosiTector.net - free web-based application offering secure storage of thickness readings	●	●
Software updates via web keep your gage current	●	●
NEW! WiFi technology wirelessly synchronizes with PosiTector.net, downloads software updates, and connects to mobile devices for expanded functionality		●
Bluetooth Wireless Technology for data transfer to a PC or optional portable printer		●
Real Time Graphing, Picture Prompting, Batch Notes and Onscreen help		●
PosiTector SPG Surface Profile Probe specific features	Standard (1)	Advanced (3)
All features shown on PosiTector SPG overview page	●	●
Statistics - Instantly calculate average, standard deviation, min/max thickness and number of readings while measuring	●	●
Hi-Lo limits audibly and visibly alerts when measurements exceed your specified limits	●	●
Reading Storage Capacity	250 in one group	100,000 in up to 1000 groups
SmartBatchÎ allows entry of user-defined parameters and criteria to comply with various standards and test methods		●

<i>PosiTector DPM Environmental probe</i> specific features	Standard (1)	Advanced (3)
All features shown on PosiTector DPM overview page	●	●
Dataset Storage Capacity (1 dataset = RH, Ta, Ts, Td, TsóTd) Stored readings can be viewed or downloaded	2,500 in one group	20,000 in up to 1000 groups
Auto Log Mode automatically records all 5 parameters at user selected time intervals. Runs unattended on batteries or continuously via USB.	●	●
Unattended battery life (using 3 AAA alkaline batteries)	up to 50 hours	up to 8 months
Stream datasets via USB or Bluetooth wireless at specified Auto Log intervals. Ideal for remote monitoring.		●
Trend Charts graph readings in real-time		●
User defined limits for all parameters with visible and audible warnings		●
<i>PosiTector 6000 Coating Thickness probe</i> specific features	Standard (1)	Advanced (3)
All features shown on PosiTector 6000 overview page	●	●
Statistics - Instantly calculate average, standard deviation, min/max thickness and number of readings while measuring	●	●
FAST mode faster measurement speed for quick inspection	●	●
SCAN mode take continuous readings without lifting the probe		●
Hi-Lo Limits audibly and visibly alerts when measurements exceed your specified limits	●	●
Reading Storage Capacity	250 in one group	100,000 in up to 1000 groups
SSPC PA2 feature set determines if film thickness over a large area conforms to user-specified min/max levels		●
PSPC 90/10 feature determines if a coating system complies with an IMO performance standard for protective coatings		●
Multiple stored calibration adjustments for measuring on a variety of substrate conditions		●