

SuperSoniX™

Highest Performance
Ambient Temperature Ultrasonic Couplant

SuperSoniX is the best water-based high performance couplant with a broad operating range and slow evaporation rate.*



PRODUCT DESCRIPTION

Gel couplant, not stringy or sticky

Gel viscosity remains in place for overhead and vertical surfaces

Broad operating range for a water-based couplant

Slow drying

Improved stability against corrosion salts

Water-soluble

Safety: Environmental and operator friendly

No formaldehydes, nitrates, nitrites or glycol ethers

Contains glycerin. Not for aluminum aircraft inspections

*For a broader (and lower) operating range and/or even slower evaporation rate than SuperSoniX, consider EchoPure.

REMOVAL: Wipe with a rag or water wash.

PRODUCT SPECIFICATIONS

Operating Range:

-10° to 220° F (-23° to 104° C)

- **Viscosity:** Medium flowable gel
- **Halogens & Sulfur:** Less than 50 ppm
- **pH:** 8.0 nominal at 20° C
- **Compliance:**
ASME Boiler & Pressure Vessel Code (T-533)
NAVSHIPS 250-1500
Nuclear Grade (< 50 ppm Halogens & Sulfur)

PACKAGING

Carton of (12) 4-oz / 118 ml bottles
Carton of (12) 12-oz / 355 ml bottles
1 gallon / 3.8 liter cubitainer
5 gallon / 19 liter cubitainer
55 gallon / 208 liter drum

ECHO ultrasonics  The couplant experts

