

EchoTherm™ Extreme

High Temperature
Ultrasonic Couplant

EchoTherm Extreme removes the industrial accident liability, personnel risk and 'startle' factor of unanticipated auto-ignition events when conducting high temperature ultrasonic inspections. If ultrasonic gaging or corrosion testing is performed in a potentially flammable or explosive atmosphere, **EchoTherm Extreme is recommended as the only couplant that will not auto-ignite under 1300°F, nor leave a residue.**



PRODUCT DESCRIPTION

The ideal couplant for inspection ports:

- No auto-ignition under 1300°F
- No minimum operating temperature

Minimal residue to interfere with subsequent inspections.

Less smoke than high-temperature couplants containing a plastic polymer.

Ultra-high temperature couplant intended to optimize sound transmission and reduce surface noise.

Does not contain plastic to melt before conducting sound:

- Instant response time
- Increases testing efficiency
- Reduces the time transducers are exposed to high temperatures

PRODUCT SPECIFICATIONS

Operating Range:

Ultrasonic flaw, corrosion and thickness:
-40° to 1250°F (-40° to 675°C)

- **Auto-ignition Temperature***: >1300°F (704°C)
*Test by John A Kennedy & Assoc., ASTM E659-14
- **Viscosity**: Thick paste

PACKAGING

ETM-EX-02:

2 fluid oz. / 4 oz. avdp (weight), metal tubes

SDS available at www.echoultrasonics.com

ECHO ultrasonics
The couplant experts

B BERG ENGINEERING & SALES CO., INC.
Your Complete Source for NDT Testing Equipment Since 1969!

3893 Industrial Avenue • Rolling Meadows, IL • 60008
phone: (847) 577-3980 • fax: (847) 577-0474
www.bergeng.com • info@bergeng.com