ECONOgel UT NDT Ultrasonic Couplant

ECONOgel is the most economical water soluble NDT ultrasonic couplant. Compatible with most metals, plastics and composites, it has good ferrous corrosion inhibition.



PRODUCT DESCRIPTION

Reduced surface tension provides fast wetting.

ECONOgel is glycerin and silicone free.

Good ferrous corrosion inhibition and is compatible with most metals, plastics and composites.

Completely salt stable. It will not thin with corrosion salts, marine environments or highway infrastructure subjected to de-icing salts.

Environmental and operator friendly. No formaldehydes, nitrates or nitrites.

PRODUCT SPECIFICATIONS

Operating Range:

26° to 120°F (-3.3° to 48°C)

Viscosity: Medium

■ Halogens & Sulfur: Less than 50 ppm

■ ASTM D808-11, ASTM D129-13, ASTM D512-12

■ Acoustic properties:

 $VL = 1.55 \text{ mm} / \mu \text{ sec}$ Z = 1.60 mRayls

PACKAGING

7 gallon (US) / 26.5 liter pail with lid/pour spout 55 gallon (US) 208 liter drum

REMOVAL: Wash with water or wipe with paper or cloth rag before couplant dries. If couplant has dried, pressure wash or use brush and running water.

SDS available at www.echoultrasonics.com





3893 Industrial Avenue • Rolling Meadows, IL • 60008 phone: (847) 577-3980 • fax: (847) 577-0474 www.bergeng.com · info@bergeng.com