

RiFlexio



pushcable color-TV-camera with turn-off module for pipes from ID 80 up to ID 200

includes following equipment:

stainless steel reel with waterproof axle
art-no. 75108




- control electronic for all camera functions and the turn-off module in water proof metal housing
- water proof camera plugs
- 50 m push cable 9,8 mm in diameter, black
- arresting brake
- guide from frictionpoor special synthetic material
- prepared for changeable cameraheads
- flexible plug-adapter
- video – out BNC
- video – in BNC
- working from 100V AC up to 240V AC
- remote control unit

turn-off module to inspect turn-off pipes

- axial-camera RI 4040 VB (self leveling picture)
with skid (art-no. 75110)
- for pipes from ID 80 up to ID 200
(art-no. 75109)
45° bends from ID 80
87° bends from ID 100



options:

	name	article	art-no.	
1	TFT-Monitor, 5,6" • justable holder on reel • robust metal – housing with sun shield		80003	
2	TFT – Monitor 5,6" with SD – cardmemory • justable holder on reel • robust metal – housing with sun shield • SD-memorycard-slot for saving of single pictures in JPG 720x480 or videosequences 800 x 600 / 25 fps PAL, MPEG - 4 • SD-card up to max. 8 GB upgrade possible (ca. 14 h video) • easy handling with integrated buttons TFT – Monitor HR 5,6" with SD – cardmemory • TFT – Monitor with better solution	 	52680 52809	
3	metercounter with displaying in the monitor • set of meters, on / off with buttons control		80005	
4	Locator • transmitter circuit board built in in reel • spool built in in camerahead • frequency 33 kHz possible (without amplifier)		52381	
5	text-generator • free text and 60 fixwords • date and time, SW-WS change • meter in picture, set of meters • keyboard with water protection		50142	

technical modification reserve, date: 01.09.2011
this price does not include handling and shipping

	Name	article	art-no.	
6	camera Saniscope RI 2325 <ul style="list-style-type: none"> • for pipes from ID 25 up to ID 125 • 87° bends from ID 40 • 5 m pushcable 4,5 mm in diameter 		86004	
7	skid 32 for RI 2325 <ul style="list-style-type: none"> • two parts screwable • 32 mm in diameter • 87° bends from ID 40 		95676	
8	skid 40 for RI 2325 <ul style="list-style-type: none"> • two parts screwable • 40 mm in diameter • 87° bends from ID 50 		51433	
9	brushskid for RI 2325 <ul style="list-style-type: none"> • two parts screwable • 87° bends from ID 70 		51432	
10	camera RI 2930 <ul style="list-style-type: none"> • for pipes from ID 50 up to ID 150 • skid from ID 50 • brushskid from ID 70 		51845	
11	skid from ID 70 for RI 2930		94024	
12	brushskid from ID 100 for RI 2930		94025	
13	camera RI 4025 Std <ul style="list-style-type: none"> • for pipes from ID 70 up to ID 300 • skid from ID 70 • brushskid from ID 100 		51937	
14	camera RI 4040 VB (vertical picture) <ul style="list-style-type: none"> • for pipes from ID 70 up to ID 300 • skid from ID 70 • brushskid from ID 100 		51938	
15	skid from ID 100 for RI 4025 and RI 4040		94002	
16	skid from ID 120 for RI 4025 and RI 4040		94005	
17	pan rotate-pushcamera RI 75120 SKS RA <ul style="list-style-type: none"> • camera size: 75 mm in diameter, length 120 mm • waterproof up to 2 bar • pan range 250°, rotation endless (slip rings) • 90° pan function • camerapicture mirrors, camerahead automatic reset • self leveling picture, remote focus • automatic shutter, LED-lighting • pan head rested with both sides bearings 		51646	
18	pushskid for RI 75120 SKS RA		96113	
19	holder for pushskid		97370	
20	wheelskid from ID 150 for RI 75120 SKS RA		96282	
21	wheelskid from ID 200 for RI 75120 SKS RA		51864	
22	cameraholder for RI 75120 SKS RA		10046	