

RI 2020 SLC












color-TV-camera (art-no. 79014)
for pipes from DN 25 - 80 (ID 1" - 3.2")
87° bends from DN 40 (From ID 1.6")

includes following equipment:

- stainless steel-camera-housing with flexible spring conr camera 20 mm in diameter, length 20 mm
- waterproof up to 1 bar
- high resolution color-camera-module with electronical shutter
- LED-lighting
- wide angle lens with sapphire – protection glass
- fixfocus adjustable (only in factory)
- 10 m (30 ft.) pushcable with 5,5 mm in diameter on rotatable reel basket
- TFT-monitor 5.6"
- metercounter in display
- battery with charger and charge indication
- video – out BNC
- transportcase
- mains power from 100V AC up to 240V AC or with built-in battery (ca. 4 h)



options:

	Name	article	art-no.	price
1	SD – card memory • SD-memorycard-slot for saving of single pictures or videosequences • SD-card 4 GB (up to max. 32 GB upgrade possible) • easy handling with integrated buttons		70175	
2	guide ball 27 • two parts screwable • 27 mm in diameter • 87° bends from DN 40 (ID 1.6")		88021	
3	guide ball 32 • two parts screwable • 32 mm in diameter • 87° bends from DN 50 (ID 2")		88022	
4	upgrade up to 25 m (80 ft.) pushcable		88023	
5	Text-Generator for RI 1320, RI 2020, RI 2325 and RI 25 SLC • free text • date and time • meter in picture, set of meters • 100 fix lines and 10 fix sides • keyboard with water protection		53165	
6	locator sonde • connectable between pushcable and camerahead • with sonde and transmitter circuit board • frequency 512 Hz		88030	
7	locator sonde • connectable between pushcable and camerahead • with sonde and transmitter circuit board • frequency 33 kHz		88025	