

RI 25 RA analog





axial-color-TV-camera (art-no. 83031)
 For pipes from DN 50 - DN 150 (ID 2" - 6")
 87° bends from DN 50 (ID 2")

includes following equipment:

- stainless steel-camera-housing with flexible spring connection, camera 25 mm
- waterproof up to 2 bar
- high resolution color-camera-module with elektronical shutter
- LED-lighting
- super-wide angle lens with sapphire - protection glass
- fixfocus from 2 up to 20 cm adjustable (only in factory)
- 30 m (100 ft.) pushcable 6,5 mm in diameter
- stainless steel reel with water proof axle
- arresting brake
- guide ball from ID 50 and guide brush from ID 70
- video - out BNC
- mains power from 100V AC up to 240V AC



options:

	Name	article	art-no.	price
1	TFT-Monitor, 5,6" • justable holder on reel • robust metal - housing with sun shield		80003	
2	TFT - Monitor 5,6" with SD - cardmemory • adjustable holder on reel • robust metal - housing with sun shield • SD-memorycard-slot for saving of single pictures or videosequences • SD-card 4 GB (up to max. 32 GB upgrade possible) • easy handling with integrated buttons		52680	
3	metercounter with displaying in the monitor • set of meters • on / off with buttons control		80005	
4	battery unit with integrated chargerunit • built-in in reel housing • working from 2 up to 4 h, charge indication		80004	
5	locator sonde • connectable between pushcable and camerahead • with sonde and transmitter circuit board • frequency 512 Hz		77033	
6	locator sonde • connectable between pushcable and camerahead • with sonde and transmitter circuit board • frequency 33 kHz		79013	
7	text-generator • free text and 60 fixwords • date and time • meter in picture, set of meters • keyboard with water protection		50142	