

# Airspray Tanks



To feed, under pressure, all Airspray automatic and manual pressure guns. Our Airspray Tanks are CE, ATEX and ASME certified. Our agitators are lub-free agitator. They are directly assembled on some tanks, but can also be easily added afterwards to any 10L, 20L or 50L tank (1).

- Easy to work with: Easy to use, easy maintenance
- New Premium Agitator: Lube-free and very high performances
- Smart Lid: User friendly and adaptable

### SPECIFICATIONS

|                         |                   |
|-------------------------|-------------------|
| Air Inlet               | 1/2" NPS          |
| Air Outlet (to the gun) | 1/4" NPS          |
| Maximum Pressure        | From 3.5 to 7 bar |
| Capacity                | from 2L to 50L    |
| Air Regulator           | 1 per tank        |
| Max Fluid Temperature   | 49°C (113°F)      |



### CONFIGURATION OF THE AIRSPRAY TANKS

| Name                                    | Capacity         | Tank Material   | Agitator | Weight         | Max Fluid Pressure | Product Output                 | Reference   |
|---|------------------|-----------------|----------|----------------|--------------------|--------------------------------|-------------|
| Airspray Tank 2L 412 TOP no agl         | 2L<br>0.5 Gal US | Aluminum        | No       | 1.2kg 2.6lbs   | 3.5 bar 50 psi     | Top 3/8" NPS                   | 182.900.000 |
| Airspray Tank 4L 537 BOT no agl         | 4L<br>1 Gal US   | Stainless Steel | No       | 4.0kg 8.8lbs   | 4.1 bar 60 psi     | Bottom 3/8" NPS                | 182.904.210 |
| Airspray Tank 10L 637 TOP no agl (2)    | 10L<br>3 Gal US  | Carbon Steel    | No       | 11.4kg 25.1lbs | 4.1 bar 60 psi     | Top 3/8" NPS                   | 182.910.100 |
| Airspray Tank 10L 637 TOP no agl        | 10L<br>3 Gal US  | Stainless Steel | No       | 11.4kg 25.1lbs | 4.1 bar 60 psi     | Top 3/8" NPS                   | 182.910.200 |
| Airspray Tank 10L 637 TOP w/agl         | 10L<br>3 Gal US  | Stainless Steel | Yes      | 13.7kg 30.2lbs | 4.1 bar 60 psi     | Top 3/8" NPS                   | 182.910.201 |
| Airspray Tank 20L 837 TOP no agl        | 20L<br>5 Gal US  | Stainless Steel | No       | 19.4kg 43.0lbs | 4.1 bar 60 psi     | Top 3/8" NPS                   | 182.930.200 |
| Airspray Tank 20L 837 TOP w/agl         | 20L<br>5 Gal US  | Stainless Steel | Yes      | 20.8kg 45.9lbs | 4.1 bar 60 psi     | Top 3/8" NPS                   | 182.930.201 |
| HP Airspray Tank 20L 837 TOP no agl     | 20L<br>5 Gal US  | Stainless Steel | Yes      | 20.2kg 44.5lbs | 7 bar 100 psi      | Top 3/8" NPS                   | 182.930.500 |
| Airspray Tank 20L 837 BOT no agl        | 20L<br>5 Gal US  | Stainless Steel | No       | 20.4kg 45.0lbs | 4.1 bar 60 psi     | Bottom 3/4" GAS                | 182.930.210 |
| Airspray Tank 20L 837 BOT w/agl         | 20L<br>5 Gal US  | Stainless Steel | Yes      | 24.0kg 52.9lbs | 4.1 bar 60 psi     | Bottom 3/4" GAS                | 182.930.211 |
| HP Airspray Tank 20L 837 BOT no agl     | 20L<br>5 Gal US  | Stainless Steel | No       | 21.2kg 46.7lbs | 7 bar 100 psi      | Bottom 3/4" GAS                | 182.930.510 |
| HP Airspray Tank 20L 837 BOT TOP no agl | 20L<br>5 Gal US  | Stainless Steel | No       | 24.0kg 52.9lbs | 4.1 bar 60 psi     | Top 3/8" NPS & Bottom 3/4" GAS | 182.930.520 |
| Airspray Tank 50L 121 TOP no agl        | 50L<br>13 Gal US | Stainless Steel | No       | 29.5kg 65.0lbs | 3.8 bar 60 psi     | Top 3/8" NPS                   | 182.950.200 |
| Airspray Tank 50L 121 TOP w/agl         | 50L<br>13 Gal US | Stainless Steel | Yes      | 29.5kg 65.0lbs | 3.8 bar 60 psi     | Top 3/8" NPS                   | 182.950.201 |
| Airspray Tank 50L 121 BOT no agl        | 50L<br>13 Gal US | Stainless Steel | No       | 29.5kg 65.0lbs | 3.8 bar 60 psi     | Bottom 3/4" GAS                | 182.950.210 |
| Airspray Tank 50L 121 BOT w/agl         | 50L<br>13 Gal US | Stainless Steel | Yes      | 26.0kg 57.2lbs | 3.8 bar 60 psi     | Bottom 3/4" GAS                | 182.950.211 |
| Airspray Tank 50L 121 BOT TOP no agl    | 50L<br>13 Gal US | Stainless Steel | No       | 29.5kg 65.0lbs | 3.8 bar 60 psi     | Top 3/8" NPS & Bottom 3/4" GAS | 182.950.220 |

(1) Except 182.910.100

(2) Benefits from a removable Stainless Steel bucket

